



To receive a calibration and/or repair quote-RMA from R.A.E. Services Inc.
Click here>> www.raeservices.com/services/quote.htm

The Professional's Choice®

SEARCH BY MODEL NUMBER

GO

HOME

ABOUT US

PRODUCTS

RANGE COMPARISON CHARTS

ACCESSORIES

CONTACT US

WHERE TO BUY

Electrical Testers



[click to enlarge]

SLM-110

Digital Light Meter

Features

- Meets CE Requirements
- One Year Limited Warranty
- Compact & Lightweight
- Easy to Operate
- Large LCD Display
- Wide Lighting Range 0 - 10,000 fc
- Cosine and Color Corrected
- Rugged ABS Plastic Housing
- Data Hold

Packaging

The SLM-110 comes packed with C-57 Carrying Case, one (1) B-4 Battery, Operating Instructions (form #200) complete with Lighting Chart and Warranty Card.

Specifications

Display:	3.5 digit LCD with 13mm (0.5") high numerals, "Lo Bat" annunciator
Sampling Time:	0.4 sec.
Overrange Indication:	Most significant digit "1" remains
Operating Environment:	0° to °C (32° to 122°F) at 80% RH
Power Supply:	SLM-110: One (1) 9V transistor type battery (NEDA #1604) Part #B-4
Battery Life:	150 hrs. typical w/standard carbon zinc battery
Dimensions:	7"H x 2.9"W x 1.2"D (180 x 75 x 30mm)
Weight:	8.5 oz. (240g)
Foot Candles:	
Range:	200/2,000/10,000 fc
Resolution:	0.1 fc
Basic Accuracy:	5%
Note:	Accuracy tested by a standard parallel tungsten lamp of 2854°



Product Manual



NIST, ISO, IEC, ANSI, NCSL, MIL-STD by www.raeservices.com

To receive a calibration and/or repair quote-RMA from R.A.E. Services Inc.
Click here>> www.raeservices.com/services/quote.htm



Where to Buy

[Printer Version](#)

residential/
commercial



utility/
industrial



voice/
datacom



auto/
marine



SEARCH PRODUCTS BY APPLICATIONS

Calibration & Repair
www.raeservices.com