



Delta P & Delta P Plus Controls

Solid-state product provides pressure drop measurement, digital display, and pressure drop control with an alarm function. Designed to provide accurate and dependable control of a pulse-cleaning timer, starting and stopping the cleaning process at the limits you choose.



Delta P and Delta P Plus Controls

- Delta P Plus offers three cleaning options:
 - 1) differential pressure cleaning (DFP),
 - 2) down-time cleaning (DTC), and
 - 3) combined differential and down-time cleaning (ALL).
 - Downtime cleaning option is available only on the Delta P Plus.
 - Delta P and Delta P Plus are available as standard equipment on the Downflo® Oval, Downflo II, Downflo WorkStations, Dalamatic®, Modular Baghouse, and Electrical Control Panels.
 - Digital 3 character display, 0.6-inch, high visibility red.
 - Solid-state electronics for reliability and long-term accuracy.
 - High, Low, and Alarm setpoints programmable from front panel.
 - User selected lockout feature to prevent unauthorized adjustment of setpoints.
 - Form C relays rated for 10 Amps at 230 VAC.
 - Accuracy $\pm 1\%$ full scale.
 - Programming retained in E²PROM with no battery required.
 - Choice of units, inches water gauge or daPa (decaPascals).
 - Jumper selected 115 or 230 VAC power.
 - No battery backup is required.
 - UL and CUL Approved.
- NIST, ISO, IEC, ANSI, NCSL, MIL-STD by www.raeservices.com

Specifications

- Power Required:** 15 VA, 115 or 230 VAC, jumper selected
- Display:** Three digits - pressure measurement or setpoints
Units of measurement - "wg or daPa
Yellow LED - indicates cleaning relay latched
Red LED - indicates alarm relay closed
- Keypad:**
- | Delta P | Delta P Plus |
|----------------|---------------------|
| ■ Low Set | ■ Menu |
| ■ High Set | ■ Set |
| ■ Alarm Set | ■ Downtime Clean |
| ■ Up Arrow | ■ Up Arrow |
| ■ Down Arrow | ■ Down Arrow |
- Pressure Range:** 0 - 10 "wg
- Relays:** Cleaning Relay - 1 NC, 1 NO, Form C, 10 Amps @ 230 VAC
Latches at High setpoint, unlatches at Low setpoint
Auxiliary Relay - 1 NC, 1 NO, Form C, 10 Amps @ 230 VAC
Mode 1: Latches at Alarm setpoint after 10 second delay, unlatches at High setpoint
Mode 2: Duplicates Cleaning Relay, no alarm function other than LED indication on front panel
- External Inputs:** Remote contact closure to lock setpoints
Remote contact closure for alarm reset/defeat
- Mounting:** Type (NEMA/UL) 4 panel mount, up to 12 gauge panel thickness (UL and CUL approved)
- Environmental:** Operating Temperature: 32 - 122°F (0 - 50°C)
Humidity: 0 - 85%, noncondensing
Altitude: 6,560 ft. (< 2000 meters)

Other Uses

- Control alarm circuits
- Flow control or other dampers
- Pressure drop measurement
- Monitor HEPA or safety filters
- Control service indicator
- Replace Photohelic®* gauge

* Photohelic is a registered trademark of Dwyer Instruments, Inc.



Donaldson.

Filtration Solutions

Donaldson Company, Inc.
Industrial Air Filtration
P.O. Box 1299
Minneapolis, MN 55440
Tel 800-365-1331(USA)
Tel 800-343-3639
dustmktg@mail.donaldson.com
www.donaldson.com

Significantly improve the performance of your collector with genuine Donaldson Torit replacement filters and parts.

Visit us at www.donaldsondynamic.com

Information in this document is subject to change without notice.

© 1999 Donaldson Co., Inc.
Printed in U.S.A. on recycled paper
Data Sheet Delta P Control (03/06)

NIST, ISO, IEC, ANSI, NCSL, MIL-STD by www.raeservices.com

