

Big Digit Hygro-Thermometers

Simultaneous display of Temperature and Humidity

Features:

- Attractive design for desktop or wall mounting
- Large LCD displays of Temperature and Humidity
- Max/Min memory with reset for Temperature and Humidity
- Switchable °C or °F temperature units
- Complete with built-in tilt stand, wall mounting bracket and AAA battery

445713 Additional Features

- Dual indoor/outdoor Temperature and Humidity displays

- Remote "outside" sensor on 35" (89cm) cable

445715 Additional Features

- Remote sensor on 35" (89 cm) cable
- User accessible temperature and humidity calibration adjustments
- Available with a NIST traceable certification
- Optional RH calibration bottles



CE

Specifications:	445703	445713	445715
Humidity range	10 to 85%RH	10 to 99% RH	10 to 99% RH
Basic RH accuracy	± 6% (25 to 80%)	± 5% (25 to 85%)	± 4% (25 to 85%)
Temperature range	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)
Basic Temperature Accuracy	+/-1.8F/1°C (14 to 122°F)	+/-1.8F/1°C (14 to 122°F)	+/-1.8F/1°C (14 to 122°F)
Dimensions	4.3x3.9x0.78" (109x99x20mm)		
Weight	6 oz (169g)		

445580-C Optional calibration salt bottles for 445715



Ordering Information:

- 445703Big Digit Hygro-Thermometer
- 445713Big Digit Indoor/Outdoor Hygro-Thermometer
- 445715Big Digit Remote Probe Hygro-Thermometer
- 445715-NIST ..Big Digit Remote Probe Hygro-Thermometer w NIST cert
- 445580-COptional 33% and 75% RH calibration bottles for 445715

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864
ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



5/05/06 - R1