

To receive a calibration and/or repair quote-RMA from R.A.E. Services Inc.  
Click here>> [www.raeservices.com/services/quote.htm](http://www.raeservices.com/services/quote.htm)



[Home](#) | [Run an Ad](#) | [Help](#) | [My LabX](#)

[About LabX](#) | [Contact](#) | [Sign In](#) | [Register](#)

[Advanced Search](#)

## Browse

[All Categories](#)  
[Announcements](#)  
[BIG Lists](#)  
[Great Deals](#)  
[LabLinks](#)  
[New Listings](#)  
[New Products](#)  
[Wanted](#)

## LabAuction

[Open LabAuctions](#)  
[New Listings](#)  
[Closing Today](#)  
[More...](#)

## Recently Viewed

1. [perkin elme...](#)

## Other LabVista For Sale

Found: Wednesday, December 31, 2008 Location: TEXAS CITY, TX, Texas, USA

[What is LabVista?](#)

**Are you interested in this Item? Register now!**

**Sign In** or **Register** to contact the advertiser. You can [Learn More](#) about LabX or read our [New User's Guide](#).



[Contact Advertiser](#)

## 1. PERKIN ELMER LAMBDA EZ201 UV/VIS SPECTROPHOTOMETER S/N: ...

1. PERKIN ELMER LAMBDA EZ201 UV/VIS SPECTROPHOTOMETER S/N: 9907018, WITH USERS MANUAL. PRODUCT SPECIFICATIONS: MONOCHROMATOR: EQUIPPED WITH HIGH RESOLUTION CONCAVE DIFFRACTION GRATING AND SEYA-NAMIOKA MOUNT. WAVELENGTH RANGE: 190 TO 1100 NM, SPECTRAL BAND PASS: 2 NM, STRAY LIGHT: 0.05% OR LESS (220 NM FOR NA1, 340 NM NANO2), WAVELENGTH ACCURACY: +/-0.3 NM, WAVELENGTH SETTING REPRODUCIBILITY: +/-0.1 NM, PHOTOMETRIC MODE: ABS = -2 TO 3 ABS %T = 0 TO 300% T, PHOTOMETRIC ACCURACY (MEASURED WITH NIST 9300 FILTER): +/-0.002 ABS (0 TO 0.5 ABS) +/-0.004 ABS (0.5 TO 1.0 ABS), PHOTOMETRIC REPRODUCIBILITY: +/-0.001 ABS (0 TO 0.5 ABS) +/-0.002 ABS (0.5 TO 1.0 ABS), BASELINE FLATNESS: +/-0.002 ABS (200 TO 950 NM), BASELINE STABILITY (2 HOURS AFTER POWER UP): WITHIN +/-0.0003 ABS/HR (AT 500 NM), RESPONSE: FAST, MEDIUM, SLOW, WAVELENGTH SCAN SPEED: 10, 100, 200, 400, 800, 1200, 2400, 3600 MN/MIN., LIGHT SOURCES: DEUTERIUM LAMP, TUNGSTEN IODIDE LAMP, LIGHT SOURCE SWITCHOVER: AUTOMATIC SWITCHOVER; INTERLOCKED WITH WAVELENGTH, SAMPLE COMPARTMENT: BEAM SPACING = 100 MM 120 (W) X 300 (D) X 140 (H) MM, DETECTOR: SILICON PHOTODIODE, DISPLAY: MONOCHROME, LIQUID CRYSTAL DISPLAY (LCD), PRINTER INTERFACE: STANDARD (ESC/P COMMAND), CARD INTERFACE: STANDARD, FOR OPTIONAL SOFTWARE, ANALOG INTERFACE: 0-1.0 V FULL-SCALE, COMMUNICATION FUNCTION: RS-232C, BIDIRECTIONAL. DIMENSIONS: 500 (W) X 560 (D) X 250 (H) MM (WITH LCD FOLDED FLAT) photo

Ad# **LV5038063**  
Item ID:  
Make:  
Model:  
Price:  
Category: **Other**

[See our for sale ads on LabX](#)

NIST, ISO, IEC, ANSI, NCSL, MIL-STD by [www.raeservices.com](http://www.raeservices.com)

To receive a calibration and/or repair quote-RMA from R.A.E. Services Inc.  
Click here>> [www.raeservices.com/services/quote.htm](http://www.raeservices.com/services/quote.htm)



[< back](#)

*Information and details contained in the listing above were updated on Wednesday, December 31, 2008.  
Please contact the advertiser using the form below for complete product details and availability.*

---

### **Bamko-Surplus**

LabX Member since May 1999. In business since 1994.

Bamko - Surplus Process Equipment - Founded in 1994 buys and sells petro-chemical process equipment from laboratory equipment to pumps, motors, pipe, valves and everything in between including entire process plants and pilot plants.

---

NIST, ISO, IEC, ANSI, NCSL, MIL-STD by [www.raeservices.com](http://www.raeservices.com)